



RANGE OF PRODUCTS

ES Professional Loudspeaker Systems

DESCRIPTION

ES MK-10, TWO WAY PASSIVE LOUDSPEAKER

FEATURES

- 2Way Full Range
- Electronically Controlled
- Cabinet made from polypropylene and special high-tech material in large injection mold.
- 10" woofer with 50mm voice coil
- Heavy duty protective grill
- Special high frequency protection
- Rotatable 90°x60° dispersion horn
- Arrayable vertically and horizontally

The MK-10 loudspeaker system is a compact device designed to perform in a wide range of public address and sound reinforcement applications. It is a 2Way passive system consisting of one proprietary 10 inch low frequency drivers and a high frequency driver with a 90x60 degrees horn, housed in a vented enclosure.

The enclosure is black and fitted with two M8 screws on top and bottom, and one M8 screws on each side. The front of the speaker is protected by a heavy duty expanded metal grill.

The MK-10 loudspeaker is designed to operate with the P 211 MK - E processor unit which contains speaker sense, drivers protection, amplitude and phase response alignment circuitry, optimized for the loudspeaker.

The P211 MK - E processor, allows the loudspeaker to be operated at full capacity with maximum fidelity and reliability.

IDEAL FOR

- Pubs,
- Clubs, Discos,
- Restaurants,
- Conference rooms,
- Multimedia,
- Malls

PROFESSIONAL LOUDSPEAKER SYSTEMS

TECHNICAL DATA

Frequency response
60 - 18'000 Hz ± 3dB

Sensitivity
95 dB 1W / 1m.

Maximum SPL
Continuous 117dB, Peak 123dB

Power Handling
Continuous 200 W / 8 Ω
Peak 400 W / 8 Ω



RANGE OF PRODUCTS

ES Professional Loudspeaker Systems

SPECIFICATIONS

ES-10 2Way passive loudspeaker

MK-10 2Way passive Compact Full Range

<i>Frequency response (1)</i>	60 - 18'000 Hz ± 3dB
<i>Maximum SPL (2)</i>	continuous 117 dB - peak 123 dB
HF Distribution pattern	
<i>Horizontal / Vertical</i>	90° (-6dB points) / 60° (-6dB points), 1KHz
Transducers	
<i>Low frequency</i>	1 x 10" cone driver AP 10 - 8Ω, 200W
<i>High frequency</i>	1 x 1.5" high frequency driver, AP HFD 02 - 8Ω, 40W
<i>Crossover</i>	LO: 2KHz 18 dB / octave, HI: 2KHz 18 dB / octave
<i>Nominal impedance</i>	8Ω
<i>Enclosure</i>	0,02 m3, vented
<i>Size / Weight</i>	310 x 530 x 345 mm (W x H x D) / 14 Kg.
<i>Finish</i>	black
<i>weather resistance</i>	IEC 529 IP 44 temperature and UV
<i>optional</i>	100-V line (transformer)

.....